## **Advantage Series**





## 3 Product/6 Hose, Pump/ Dispenser

B05202 Dispenser 3 Product,6 Hose B15202 Pump 3 Product,6 Hose

## Standard Feature

- -Luxurious & modular high hose designed by Gilbarco USA
- -Stainless steel side sheathing with ABS injection plastic main access doors
- -Durable low noise G-rotor pump(selfcontained models only)
- -High accurate four piston flow meter designed by GiIbarco USA
- -Highly readable 1 inch back light LCD display
- -Reliable PCB which can interface TS/1000
- -Three level filtering system to secure purity of the dispensed oil
- -Ex-proof metal conduit greatly increases the safety of wire connection
- -Mechanical totalizer

## **Specifications**

Measurement in liters
Standard flow rate: 50L/Min
High flow rate: 65L/Min
Measure accuracy:±0.25%
Working environment

Relative humidity: 20%~95%

Ambient temperature: -35℃~+55℃

Unit noise rate: ≤72dB

Power supply for computer:1 phase, 220V, 50Hz

Power consumption for computer:≤500W Inlet vacuum rate for suction pump:≥54Kpa

Outlet pressure rate for STP:≥260Kpa

Power supply:

3 phase, 380V, 50Hz for self-contained model

1 phase, 220V, 50Hz for STP

Dimension: 1250(L)X882(W)X2387(H)mm

